

# Temperature USB PDF Data Logger TEMPOD 200X

DS-PO200X-170504



## AUTO PDF REPORT WITH EMBEDDED RAW DATA

Automatically generated encrypted PDF format report, no software required to access data file. Embedded raw data allows further data processing via TempSen cloud and 3rd party system.



## SOFTWARE-FREE ONLINE CONFIGURATION

Allows rapid online configuration without installing specific programming software, multiple platforms compatible.



## INTUITIVE LCD INDICATION

LCD presents all key information including recording statistics, alarm and running status, remaining battery volume.



## MULTIPLE ALARM RANGES

Up to 5 alarm ranges offer detailed and precise temperature excursion statistics.



## PASSWORD PROTECTION

Enable password protection to prevent unauthorized manipulation to device.

## IP65

## IP65 RATING

Thorough protective design ensures logger continuously and stably works in complex environments.



USB 2.0



External RTD Probe Cable: Teflon, 1m

## SPECIFICATIONS

Type	Multi-use
Sensor	Temperature: External RTD sensor (1m)
Memory Capacity	28800 readings
Measurement Range	-200°C...70°C
Accuracy	±0.5°C (-100°C...70°C) ±1.0°C (other range)
Resolution	0.1°C / °F
Start Mode	Manual / Auto / Temperature start
Logging Interval	1 minute...2 hours
Alarm Range	High and low alarms / 5 alarm ranges
Battery	3.0V lithium battery, user replaceable
Battery Life	18 months
Display	LCD •OK(√), Alarm(x), alarm zone •Running status •Temperature statistics (max, min, avg) •Remaining battery level •Mark history
Connection	USB 2.0 Connector
Automatic Data File	Encrypted PDF report with embedded raw data
Software	TempCentre2 (21 CFR 11 compliant)
Calibration	Factory NIST traceable 3-point calibration
Certifications	CE, FCC, RTCA-DO160G, IATA PI970 II, RoHS, WEEE
Protection Class	IP65
Dimensions	100mm L x 40mm W x 12mm H
Weight	Approx. 68g
Packaging/ Material	Case / Polycarbonate

## FEATURES

- ✓ USB connector allows downloading data without reader or cable
- ✓ Repeat start enables launching new recording immediately without configuration
- ✓ Time mark for events requiring special attention
- ✓ Firmware user upgradable
- ✓ IATA PI970 II compliant, your goods with Tempod inside will not be handled as dangerous goods
- ✓ RTCA DO-160G compliant allows monitoring in air freight
- ✓ GxP regulations compliant

## APPLICATIONS

