



### Data Report

**File Information**  
 File Created Date: 09/03/19 11:34:26  
 Note: All Times shown are based on UTC+10:00 and 24h

**Device Information**  
 Device Type: Temperature logger  
 ID: TH1907000593  
 Start Delay: 20 min  
 Description: Temp Recorded

**Logging Summary**  
 First Point: 06/28/19 06:45:04  
 Stop Time: 05/03/19 11:25:04  
 Number of Points: 893  
 Trip Length: 064 04h 40m 00s  
 Stop Mode: Manual Stop

**Alarm Condition**  
 First Point Time  
 Over 78.0 00/00/00 00:00:00  
 Below -30.0 00/00/00 00:00:00




- Auto Generated PDF & CSV Reports
- Integrated USB
- Replaceable Battery
- User Programmable
- Validation Certificate Included

# Tempnote® T32


Multi Use Temperature Data Logger


## Economical Reusable Temperature Data Logger for Cold Chain Monitoring


Tempnote® T32 dataloggers are extremely engineered for cold chain monitoring during storage or transit. Tempnote® T32 is integrated with USB & Plug-N-Play features for auto-generating secured PDF report without requiring additional Hardware (cable/interface) or software. Tempnote® T32 dataloggers are equipped with highly precise sensor with accuracy of  $\pm 0.5^{\circ}\text{C}$  for entire range of  $-25^{\circ}\text{C}$  to  $+60^{\circ}\text{C}$ . Manufacturer's NIST traceable Certificate of Validation is included to comply with Quality Assurance needs.


- 

**PDF & CSV REPORT**  
 Automatically generated encrypted PDF & CSV format report, no software required to access data file.
- 

**VALIDATION CERTIFICATE**  
 Manufacturer's Validation Certificate included for proven accuracy and to comply with regulations
- 

**EN 12830 COMPLIANT**  
 Compliant with European standards to meet the demands of the transportation industries
- 

**INTUITIVE LCD INDICATION**  
 LCD shows vital information including statistics, alarm and running status, remaining battery
- 

**USB CONNECTION**  
 Integrated USB for most conveniently download data report without additional interface or cable.
- 


**IP65 RATING**  
 Highest Protective design ensures continuous data logging even in complex environmental conditions.



Intuitive LCD Screen

LED Indicator

USB Cap




Start / Stop Buttons

Battery Replacement Cap



## Technical Specifications

Type	Re Usable / Multiple Use	Protection Class	IP65
Measurement Range	-25°C to +60°C	Dimension	83 mm x 36 mm x 14 mm
Accuracy	± 0.5 °C (-25°C to +60°C)	Weight	Approx 39 Gms
Resolution	0.1 °C	Certifications	EN12830, CE
Memory Capacity	32,000 Values	Validation Certificate	Hard Copy Included
Start Mode	By Button or Time Start	Report	Self Generated PDF + CSV
Recording Interval	10 sec to 18 Hrs (Customizable)	Alarm Range	High & Low Alarm
Battery Type	3V / Replaceable CR2032	Connectivity	USB 2.0



## Application

Sea Freight & Air Freight



Distribution & Last Mile Delivery



Storage & Freezer Monitoring



Download Calibration Certificate



01 Visit [www.tempnote.com](http://www.tempnote.com) and enter device ID  
02 PDF copy of certificate will be available to download