Tempnote®





Real-Time Data Logger & Tracker|5G GSM Based











- New generation of global real-time temperature monitor
- (>) Data is stored in the cloud for traceability; Micro USB port for backup PDF data download
- (>) Full cold chain visibility (Location, Temperature, Route, Shock, Tilt) via Frigga cloud
- (>) Improve transportation efficiency and reduce products loss with real-time monitoring
- (24/7 data control & analysis, manage quality and control of your products in-transit via Real time alert on SMS, Email and APP
- Support weak light detection, protect the safety of your goods effectively



PDF & CSV REPORTS

Encrypted PDF & CSV format report can be generated from cloud platform at any given time.



Splash Resistance

Best in class protection against the moisture and water splash.



5G Network

T71 works on 5G network to ensure reliable connectivity to cloud.



VALIDATION CERTIFICATE

Manufacturer's Validation Certificate included for proven accuracy and to comply with regulations



INTUITIVE LCD INDICATION

LCD shows vital information including statistics, alarm and running status, remaining battery



FDA 21CFR Part 11 Compliant

Complies with FDA 21CFR part 11 standards, ensuring data integrity

Technical Specifications

Usage Type	Multi-use
Monitor Information	Temperature, Location, Track Routes, Shock, Tilt,
Temperature Sensor	External Sensor Probe (1 meter)
Temperature Measurement Range	-40°C ~ +80°C
Temperature Accuracy Range	± 0.5 °C (-20°C ~ +40°C); ± 1 °C for other range
Resolution	0.1°C
Memory Capacity	Max. 50,000 readings
Location Type	LBS Base Station Positioning
Cellular	Vodafone network.
SIM Card	Internal Embedded (Global Data Roaming)
Battery	lithium ion
Use Time	120 Days with 120 Min. reporting interval in single charge
Data Logging Interval	10 Min. (settable via cloud platform)
Data Reporting Interval	10 Min. (settable via cloud platform)
Environmental Rating	IP64
Report	Get PDF Report Via Micro USB/ Frigga Cloud Platform
Mobile Application	Frigga Track (Android/IOS)
Dimensions/Weight	103 x 65.6 x 18.5 mm / 250 grams
Certifications	FCC,CE,RTCA/DO-160G,UN38.3,ROHS,WEEE
Alarm Range	High & Low Alarm (Cloud Programmable)















IND

Tempnote Pvt. Ltd., Ahmedabad GJ 382481 +91-99988 41181 | info@tempnote.com

USA

Tempnote Inc., Tucker GA 30084 +1-502 956 2685 | info@tempnote.com

