

## Data Report

### File Information

File Created Date: 2022-02-11 24:25

### Device Information

Device Type:  
ID:  
Serial Number:  
Description:

### Logging Status

First Point:  
Stop Time:  
Number of Points:  
Trip Length:  
Stop Mode:

### Alarm Condition

Alarm Type:  
Alarm Level:



# T32

Multi-use  
Temperature Data logger

- Auto Generated Secured PDF & CSV Reports
- Integrated USB
- FDA 21CFR part 11 Compliant Software
- User Programmable
- Validation Certificate Included

**300+** DAYS  
RUNTIME  
Supports longest Recording Period in-transit

## Robust Multi-use Temperature Data Logger for Reliable Cold Chain Monitoring

Tempnote® T32 data logger is expertly designed for reliable cold chain monitoring during transit. It features integrated USB and Plug-N-Play capabilities, enabling automatic generation of secure PDF and CSV reports without the need for additional hardware (such as cables or interfaces) or software. It complies with FDA 21 CFR part 11, ensuring data integrity, and is RTCA DO-160G certified ensuring it meets airline requirements for seamless acceptance without the need for any additional documentation.



### PDF & CSV REPORTS

Automatically generated encrypted PDF & CSV format report, no software required to access data file.



### VALIDATION CERTIFICATE

Manufacturer's Validation Certificate included for proven accuracy and to comply with regulations



### EN 12830 COMPLIANT

Compliant with European standards to meet the demands of the transportation industries



### INTUITIVE LCD INDICATION

LCD shows vital information including statistics, alarm and running status, remaining battery



### USB CONNECTION

Integrated USB for most conveniently download data reports without additional interface or cable.



### FDA 21CFR Part 11 Compliant


Complies with FDA 21CFR part 11 standards, ensuring data integrity



## Technical Specifications

Model	Tempnote T32
Type	Multi-use
Measurement Range	-30°C to +70°C
Accuracy	±0.5 °C (-30 °C to +70°C)
Resolution	0.1 °C
Memory Capacity	32,000 values
Start Mode	By Button or Time Start
Recording Interval	10 Sec. to 18Hrs (Customizable)
Battery Type	3V / Replaceable CR2032
Protection Class	IP65
Dimensions	89 mm x 36 mm x 16 mm
Weight	Approx 30 Gms
Certifications	EN12830,CE, RTCA-DO160G
Validation Certificate	Hard Copy Included
Report Formats	Self Generated PDF + CSV
Alarm Range	High & Low Alarm
Connectivity to PC	USB 2.0

## Seamless to operate

**1** Press  Button for 3 Seconds to Start



**2** Add Tempnote T32 to your shipment



**3** Connect Stopped directly to USB Port



**4** Automated PDF & CSV reports with all Details



### IND

Tempnote Pvt. Ltd., Ahmedabad GJ 382481  
+91-99988 41181 | info@tempnote.com

### USA

Tempnote Inc., Tucker GA 30084  
+1-502 956 2685 | info@tempnote.com

Tempnote Inc., USA

©2024, All Rights Reserved.

www.tempnote.com



Tempnote Inc., Headquartered in Atlanta, USA, along with its subsidiary Tempnote Pvt. Ltd. in Ahmedabad, India, are Leading providers of Cold Chain Monitoring and Cold Chain Packaging Solutions. They offer a wide range of monitoring devices and solutions, catering to industries like life sciences and food to ensure the safe transit and storage of temperature-sensitive goods. Tempnote reserves the right to alter product specifications and information without prior notice. Tempnote and Insupod are registered trademarks of Tempnote Inc. and Tempnote Pvt. Ltd.

DOC#T32/210724/VER1