Tempnote[®]



Per Port of Indian Conductors

Logarina St First First

Multi-use Temp & Humidity Data logger

- (>) Auto Generated Secured PDF & CSV Reports
- (>)Integrated USB
- >FDA 21CFR part 11 Compliant Software
- (>) User Programmable
- Validation Certificate Included

SUDDAYS

RUNATIME
Supports longest Recording Period in-transit

Robust Multi-use Temperature & Humidity Data Logger for Reliable Cold Chain Monitoring

Tempnote® TH32 data logger is expertly designed for reliable cold chain monitoring during transit. It features integrated USB and Plug-N-Play capabilities, enabling automatic generation of secure PDF and CSV reports without the need for additional hardware (such as cables or interfaces) or software. It complies with FDA 21 CFR part 11, ensuring data integrity, and is RTCA DO-160G certified ensuring it meets airline requirements for seamless acceptance without the need for any additional documentation.



PDF & CSV REPORTS

Automatically generated encrypted PDF & CSV format report, no software required to access data file.



VALIDATION CERTIFICATE

Manufacturer's Validation Certificate included for proven accuracy and to comply with regulations



EN 12830 COMPLIANT

Compliant with European standards to meet the demands of the transportation industries



INTUITIVE LCD INDICATION

LCD shows vital inforamtion including statistics, alarm and running status, remaining battery



USB CONNECTION

Integrated USB for most conviniently download data reports without additional interface or cable.



FDA 21CFR Part 11 Compliant

Complies with FDA 21CFR part 11 standards, ensuring data integrity

Tempnote®

TH32

-		1.0	• • •		
Lec	hnica	ıl Sn	eciti	cati	ons
		II JP	CCIII	Cuti	0113

Model	Tempnote TH32		
Type	Multi-use		
Measurement Range	-30°C to +70°C		
Accuracy	±0.5 °C (-30 °C to +70°C)		
Resolution	0.1 °C		
Humidity Range	0% rh to 100% rh		
Accuracy	± 3% rh (20%rH to 80%rh)		
Memory Capacity	32,000 values		
Start Mode	By Button or Time Start		
Recording Interval	10 Sec. to 18Hrs (Customizable)		
Battery Type	3V / Replaceable CR2032		
Protection Class	IP65		
Dimensions	89 mm x 36 mm x 16 mm		
Weight	Approx 30 Gms		
Certifications	EN12830,CE, RTCA-DO160G		
Validation Certificate	Hard Copy Included		
Report Formats	Self Generated PDF + CSV		
Alarm Range	High & Low Alarm		
Connectivity to PC	USB 2.0		

Seamless to operate

Press • Button for 3 Seconds to Start



2 Add Tempnote TH32 to your shipment



Connect Stopped logger directly to USB Port







4 Automated PDF & CSV reports with all Details













AeroLogic

AIRFRANCE /



IND

Tempnote Pvt. Ltd., Ahmedabad GJ 382481 +91-99988 41181 | info@tempnote.com USA

Tempnote Inc., Tucker GA 30084 +1-502 956 2685 |info@tempnote.com Tempnote Inc., USA ©2024, All Rights Reserved.

www.tempnote.com

